

Mayalit

Mayalit
No,A17, Xianghe West Rd., Dongjiang ind. Zone
Shuikou, Huizhou, Guangdong 516005, China
T: +86-752-533-3102
E: overseas@mayalit.com
<http://www.mayalit-intl.com>



Ben

Original color temperature adjustment technology,
an exhibition lighting product that integrates architectural
aesthetics with technological innovation.




Ben

Track Spotlight


Aesthetic Design of Geometric Appearance Focusing on Lighting Function

The design concept comes from Mondrian
Pure straight lines existing solely in vertical and horizontal forms, transcending
the abstract to become concrete, building a dynamic balance of opposition and unity.




Golden Ratio Design Exquisite Form

Following the Fibonacci sequence,
the golden section ratio, creating a visual focal point ,
building a balanced and natural aesthetic



Architectural Art Aesthetic of Order

Referring the forms of artistic architecture, the geometric volumes are skillfully stacked,
not excessively, not exaggerated, and then cleverly integrated into the inherent order of the building.
It is simple, pure, natural and focusing more on lighting function itself.



EFT™ Color Temperature Control Technology

Efficient Fine Tune

It is pioneered by Mayalit Lighting, designed specifically for exhibition lighting application scenarios, basing on dual-color temperature mixing algorithm, optimizes precise color temperature tuning method.



EFT Tunable white

The Spotlights are preset at 2700K/3000K/3500K/4000K, allowing for quick adjustment of color temperature to the preset values. If there is a color temperature deviation during actual use or in situations where higher precision is required, the color temperature can be fine-tuned in 10K increments to ensure visual consistency of the light and shadow.

Traditional Tunable white


The deviation of light source and driver electronic components manufacturing objectively exists, traditional dial code adjustment or knob adjustment may have a large color temperature difference.

Dual Optics Soft and Comfortable

TIR total internal reflection+compound eye optical system achieved light efficiency > 90%
Compound eye matrix distributed grid design,discretes focal points , and reduces stray light, extremely accurate light control, no secondary light spots.



The optical system composed of TIR collimating lens and compound eye integral lens can make the light even and soft, effectively reduce glare, and enhance the visual comfort of the audiences.



Compound Eye Optical System

TIR Lens




Press to Switch Lenses Self-locking Combinations

Press-to-change lens design,
quick switching and easy to operate.
Combinations could be self-locking,
easy maintenance.


8 Types of Optics Rich Applications

8 types of optics options, with a natural transition of light spots and no despersion light.
Rich application scenarios make exhibition setup more flexible.



Accessible to multi-platform intelligent dimming system, can flexibly adapt to various exhibition needs

It supports the customization of wired/wireless remote control protocols according
to different intelligent systems, achieving automatic control of single light/group
and intelligent interactive experiences with sound, light, and electricity.



Flexible Fine-tuning Excellent Display



90° vertical adjustment


Precise positioning,
suitable for more exhibition lighting scenarios

360° horizontal rotation

With a flexibility of 360° rotation,
it can illuminate a broader exhibition space,
meeting more needs of exhibition lighting.

Swivel Hinge and Locking Mechanism


Achieve the optimal torque value through repeated mechanical experiments.
Vertical adjustment of the swivel axis, smooth and easy to adjust,
the pendulum angle position remains constant.
In scenarios such as high altitudes, severe shaking,
and harsh environments, the shaft locks in place to ensure safety.



**Spectrum Pure
Cherish and Protect Exhibits**


Adopting SMD light sources at the leading international level, carefully selecting light color BIN zones suitable for exhibition and display needs.

Passed the ANSI/ITE TM-30-18 test standard, key parameters such as color tolerance, color gamut index, and color fidelity have all reached the leading level requirements for exhibition lighting products.



100% Independently Developed High-quality Drivers


Self-developed high-quality drivers that high-precision components from first-line brand.
The overall lifespan reaches up to 50,000 hours, ensuring long-term stable operation.




Multiple Power Options to Meet High-altitude Applications


12-18W multiple power options,can cover a spatial range of 3-20 meters and satisfy most exhibition lighting scenarios

Fixed Color Temperature



Tunable White






Ben - Track Spotlight


MBL40515

Wattage : 15W
Input Voltage : 220-240V~50/60Hz
Installation : Track mounted
Adjustable : Horizontal360°/ Vertical90°
Weight : 0.55kg
Finish : MBK/MWT








Accessory



Specification



Lighting tool




Ben - Track Spotlight



MBL40923

Wattage : 23W
Input Voltage : 220-240V~50/60Hz
Installation : Track mounted
Adjustable : Horizontal360°/ Vertical90°
Weight : 0.86kg
Finish : MBK/MWT







Accessory




Specification



Lighting tool






Ben - Track Spotlight


MBL41228

Wattage : 28W
Input Voltage : 220-240V~50/60Hz
Installation : Track mounted
Adjustable : Horizontal360°/ Vertical90°
Weight : 0.86kg
Finish : MBK/MWT



Accessory



Specification



Lighting tool




Ben - Track Spotlight



MBL41648

Wattage : 48W
Input Voltage : 220-240V~50/60Hz
Installation : Track mounted
Adjustable : Horizontal360°/ Vertical90°
Weight : 1.43kg
Finish : MBK/MWT


Accessory




Specification



Lighting tool






Ben - Track Spotlight
MBL40413


Wattage : 13W
Input Voltage : 220-240V~50/60Hz
Installation : Track mounted
Adjustable : Horizontal360°/ Vertical90°
Weight : 0.86kg
Finish : MBK/MWT

Specification





3000K Ra97
4000K Ra95

Accessory




Lighting tool



Ben - Track Spotlight
MBL40924


Wattage : 24W
Input Voltage : 220-240V~50/60Hz
Installation : Track mounted
Adjustable : Horizontal360°/ Vertical90°
Weight : 1.43kg
Finish : MBK/MWT

Specification





3000K Ra97
4000K Ra95

Accessory



Lighting tool






Ben - Track Spotlight


MBL41624CT (Tunable White)

Wattage : 24W
CCT : 2700K ⇄ 3000K ⇄ 3500K ⇄ 4000K
Input Voltage : 220-240V~50/60Hz
Installation : Track mounted
Adjustable : Horizontal360°/ Vertical90°
Weight : 0.86kg
Finish : MBK/MWT



Accessory



Specification



Lighting tool




Ben - Track Spotlight


MBL42445CT (Tunable White)

Wattage : 45W
CCT : 2700K ⇄ 3000K ⇄ 3500K ⇄ 4000K
Input Voltage : 220-240V~50/60Hz
Installation : Track mounted
Adjustable : Horizontal360°/ Vertical90°
Weight : 1.43kg
Finish : MBK/MWT


Accessory




Specification



Lighting tool






Ben - Track Spotlight
MBL40408CT

Wattage : 8W
CCT : 2700K ⇄ 3000K ⇄ 3500K ⇄ 4000K
Input Voltage : 220-240V~50/60Hz
Installation : Track mounted
Adjustable : Horizontal360°/ Vertical90°
Weight : 0.86kg
Finish : MBK/MWT

Specification





3000K Ra97
4000K Ra95

Accessory




Lighting tool



Ben - Track Spotlight
MBL40812CT (Tunable White)


Wattage : 12W
CCT : 2700K ⇄ 3000K ⇄ 3500K ⇄ 4000K
Input Voltage : 220-240V~50/60Hz
Installation : Track mounted
Adjustable : Horizontal360°/ Vertical90°
Weight : 1.43kg
Finish : MBK/MWT

Specification



3000K Ra97
4000K Ra95

Accessory



Lighting tool

